

SCHÖNOX HPS 92

CREATE A BOND THAT'S FINAL FOR VINYL.



ACRYLIC ADHESIVE FOR RESILIENT FLOORING

Schönox HPS 92 is designed specifically for resilient flooring, suitable for bonding of vinyl composition tile, vinyl enhanced floor tile, solid vinyl floor tile, luxury vinyl tile and planks on porous and nonporous substrates in interior areas. HPS 92 is suitable for installations with moisture levels up to 92 RH/11 pH.

©2020_SCHÖNOX_HPS_92_SELLSHEET_20-775



SCHÖNOX HPS 92

ACRYLIC ADHESIVE FOR RESILIENT FLOORING

Suitable for bonding of vinyl composition tile, vinyl enhanced floor tile, solid vinyl floor tile, luxury vinyl tile and planks on porous and nonporous substrates in interior areas. Up to 92 RH/11 pH.



CASTOR WHEEL LOADING



TROWELABLE



INTERIOR WALL & FLOOR



RADIANT HEAT

PRODUCT CHARACTERISTICS

- Faster cure time, loading in 48 hrs.
- 92% RH
- Easy to apply
- Low odor
- VOC compliant
- High strength
- High coverage
- For interior use only

RECOMMENDED APPLICATION DETAILS

Schönox HPS 92 is suitable for installing: Vinyl composition tile, vinyl enhanced floor tile, solid vinyl floor tile, luxury vinyl tile and planks on suitable, cement based substrates in interior areas

PACKAGING

- 4 gallons in plastic container

STORAGE

- Store in cool, frost-free conditions
- Shelf life: 1 year unopened
- Containers that have been opened should be closed immediately
- Remove any skin that has formed; do not stir in

TECHNICAL DATA

- Basis: acrylic dispersion with bonding additives
- Color: tan
- Density: approx. 1.20 kg/l
- Storage temperature: not below 41°F
- Working temperature: not below 59°F
- Open time: approx. 120 minutes
- Drying time: approx. 48 hours
- Final strength (prior to maintenance routine): 5 days
- Coverage per 4 gal. unit when applied with notched trowel 1/32" x 1/16" x 1/32": 1280 sq.ft.

All values are approximate and are subject to local climatic fluctuations based upon conditions at 70°F with atmosphere of less than 65% relative humidity.

DISPOSAL

Empty containers and dispose of in accordance with federal, state and local waste disposal regulations.

VOC CONTENT

0g/l (calculated), SCAQMD 1168

PRECAUTIONS

- Follow the product data sheets for the Schönox supplementary products mentioned and used.
- If in doubt, please obtain further manufacturer's information or test in a small area. Avoid eye and skin contact. Close container after each use. Do not reuse container. Do not flush adhesive down drains, sewers or waterways. KEEP OUT OF REACH OF CHILDREN. Carefully read and follow all cautions and warnings on product label. For complete safety information, please refer to the Safety Data Sheet, or visit our website, hpsubfloors.com.



LEED V4

May help contribute to LEED v4 certification of projects in these categories:

- EQc2 – 3 points Low-Emitting Materials
- MRc1 – up to 2 points Life-Cycle Impact Reduction
- MRc2 – 1 point Environmental Product Declaration
- MRc4 – 1 point Material Ingredient

