

SOME REPAIR COMPOUNDS  
AREN'T ALL THEY'RE  
CRACKED UP TO BE.  
**YOU NEED SCHÖNOX.**



### ENGINEERED FOR CRITICAL REPAIRS AND DEADLINES

Sometimes simply pouring a self-leveler over a badly damaged floor is not the answer. For long-lasting solutions, you want Schönox ÖN IT. Schönox RF cement based, fast setting and dust reduced repair mortar is designed for rapid drying patchment up to 2" on cement and gypsum substrates. Schönox PL cement based repair mortar is suitable on gypsum and cement in interior and exterior areas. SEZ Plus, our pumpable, rapid setting sand cement screed and trench filler, is ready for covering in as little as 24 hours. Use Schönox SGH rapid curing, two-part crack repair compound for filling dormant cracks, saw cuts or dummy joints.

©2020, HPS. RF, PL, SEZ PLUS, SELL SHEET, 20-765



# SCHÖNOX RF, PL, SEZ PLUS AND SGH

## LONG-LASTING SOLUTIONS FOR YOUR CRITICAL REPAIR PROJECTS

Schönox RF, PL, SEZ Plus and SGH are engineered to do more than just fill your repair needs. To lay a long-lasting foundation for Schönox self-levelers, you want Schönox repair compounds ÖN IT.



### SCHÖNOX RF

Schönox RF is excellent for ramping, filling cracks and holes, or for repairing concrete stairs. For interior use only.

- Pot life: approx. 15 minutes at 68°F
- Ready for foot traffic after approx. 60 min.
- Can be installed up to 2", finer aggregates
- Ready for covering after approx. 2 hours
- Working temperature is no lower than 41°F floor temperature
- Dust reduced
- 33 lb. net weight in paper bags



### SCHÖNOX SGH

Two component repair compound. Non shrinking, silicate based. Suitable for filling of cracks and joints and for binding nail battens and metal sections. Low odor and easy handling, ready for pour over after 1 hour. Simply pour component B into bottle containing component A and shake intensively for a minimum of 15 seconds. Use immediately after mixing.

- Part A: 300 ml
- Part B: 300 ml
- For interior and exterior use

- Working temperature is no lower than 41°F floor temperature
- Suitable for use with subfloor heating systems
- Ready for foot traffic after approx. 30 min.
- Fully loadable after approx. 24 hours
- Renovation clips included

### SCHÖNOX SEZ PLUS

Schönox SEZ Plus is suitable for installations of cement based rapid setting sand cement screeds. Ready for covering after approx. 24 to up to 72 hours (depth and other conditions may increase the amount of waiting time for covering). For interior use only.

- Compressive strength of 6500 PSI
- Coverage: approx. 18 sq.ft. per unit at a thickness of 1/2"
- Pot life: approx. 30 minutes at 68°F
- Working temperature is no lower than 41°F floor temperature
- Trench filler
- Low shrinkage
- Suitable for use with subfloor heating systems
- 55 lb. net weight in paper bags

### SCHÖNOX PL

Schönox PL is a cement based universal repair mortar for use on deep fill on cement floors. High physical properties with minimal shrinkage. Ideal for balconies, terraces, swimming pools and other outdoor wet areas. Schönox PL is suitable for leveling, smoothing and repairing of concrete, masonry cement and rapid cement screeds, ceramic tile, and old substrates with water-resistant adhesive residues. For interior and exterior use.

- Pot life: approx. 15 minutes at 68°F
- Ready for foot traffic after approx. 60 min.
- Can be installed up to 2"
- Ready for covering after approx. 4 – 16 hours, dependent upon material
- Working temperature is no lower than 41°F floor temperature
- Suitable for use with subfloor heating systems
- 55 lb. net weight in paper bags



May help contribute to LEED v4 certification of projects in these categories:

- EQc2 – 3 points Low-Emitting Materials
- MRC1 – up to 2 points Life-Cycle Impact Reduction
- MRc2 – 1 point Environmental Product Declaration
- MRc4 – 1 point Material Ingredient

Take your business to a whole new level. Call 855.391.2649 or visit [hpsubfloors.com](http://hpsubfloors.com) to learn how your projects run smoother with Schönox Ön It.

