

I Adhesive Recommendation

Amtico I



Substrate Preparation

Substrates (for example)	Gypsum based substrates	Concrete / Cement based substrates	Prefabricated boards (OSB, particle board)
Primer (for example)	SCHÖNOX KH FIX (EC1 PLUS)	SCHÖNOX VD (EC1 PLUS)	
Self Leveling Compound (for example)	SCHÖNOX AP (EC1 PLUS) SCHÖNOX ZM (EC1 PLUS R) SCHÖNOX US (EC1 PLUS R)		

Floor Covering Installation

Quality	Amtico	
Loading	Normal up to increased load (commercial areas) classes 21-23 / 31-34 / 41-42	
Recommended Adhesive	SCHÖNOX EMICLASSIC™ Universal Pressure Sensitive Acrylic Adhesive for all Flexible Coverings (EC1 PLUS)	SCHÖNOX PU 900 2-Component Universal Polyurethane Adhesive (EC 1 PLUS R)
Tool	Notched trowel 1/16" x 1/16" x 1/16"	Notched trowel 1/8" x 1/8" x 1/16"
Coverage	approx. 500 - 700 sq. ft. per unit of 3.35 gal.	approx. 105 sq. ft. per unit of 1.09 gal.

Please follow the technical information of relevant SCHÖNOX product data sheets, the advices of the manufactures of floor covering and also according to the well-known guidelines and instructions. If in doubt please do some practical tests or call the technical service under phone +49 2547 910325. More detailed information, product data sheets or laying instructions are available under www.schonox.com or www.amtico.de



I Adhesive Recommendation

Linoleum

Forbo Flooring GmbH I



Substrate Preparation

Substrates (for example)	Gypsum based substrates	Concrete / Cement based substrates	Prefabricated boards (OSB, particle board)
Primer (for example)	SCHÖNOX KH FIX (EC1 PLUS)	SCHÖNOX VD (EC1 PLUS)	
Self Leveling Compound (for example)	SCHÖNOX AP (EC1 PLUS) SCHÖNOX ZM (EC1 PLUS R) SCHÖNOX US (EC1 PLUS R)		

Floor Covering Installation

Linoleum	Artoleum, Desk Top, Marmoleum, Marmoleum Decibel, Corklinoleum, Linoflex, Bulletin Board ¹		
Recommended Adhesive	SCHÖNOX EMICLASSIC™* Universal Pressure Sensitive Acrylic Adhesive for all Flexible Coverings (EC1 PLUS)		SCHÖNOX UNITECH* Multipurpose Adhesive for carpet, vinyl and linoleum
Tool	Notched trowel 1/8" x 1/8" x 1/16" or /32" x 3/32" x 3/32"		Notched trowel 1/8" x 1/8" x 1/16" or /32" x 3/32" x 3/32"
Coverage	approx. 320 -430 sq. ft. per unit of 3.35 gal.		approx. 450 sq. ft. per unit of 3.77 gal.

Please follow the technical information of relevant SCHÖNOX product data sheets, the advices of the manufactures of floor covering and also according to the well-known guidelines and instructions. If in doubt please do some practical tests or call the technical service under phone +49 2547 910325. More detailed information, product data sheets or laying instructions are available under www.schonox.com or www.forbo-flooring.de

¹ only for SCHÖNOX EMICLASSIC

* For using in industrial areas or load of forklift trucks and elevation trucks please contact the technical service of SCHÖNOX



I Adhesive Recommendation



Vinyl

Forbo Flooring GmbH I

Substrate Preparation

Substrates (for example)	Gypsum based substrates	Concrete / Cement based substrates	Prefabricated boards (OSB, particle board)
Primer (for example)	SCHÖNOX KH FIX (EC1 PLUS)	SCHÖNOX VD (EC1 PLUS)	
Self Leveling Compound (for example)	SCHÖNOX AP (EC1 PLUS) SCHÖNOX ZM (EC1 PLUS R) SCHÖNOX US (EC1 PLUS R)		

Floor Covering Installation

Vinyl	Step, Eternal wood/form, Novilon, Novilux	
Recommended Adhesive	SCHÖNOX EMICLASSIC™ Universal Pressure Sensitive Acrylic Adhesive for all Flexible Coverings (EC1 PLUS)	SCHÖNOX UNITECH Multipurpose Adhesive for carpet, vinyl and linoleum
Tool	Notched trowel 1/16" x 1/16" x 1/16"	Notched trowel 1/16" x 1/16" x 1/16"
Coverage	approx. 500 - 700 sq. ft. per unit of 3.35 gal.	approx. 630 sq. ft. per unit of 3.77 gal.

Please follow the technical information of relevant SCHÖNOX product data sheets, the advices of the manufactures of floor covering and also according to the well-known guidelines and instructions. If in doubt please do some practical tests or call the technical service under phone +49 2547 910325. More detailed information, product data sheets or laying instructions are available under www.schonox.com or www.forbo-flooring.de



I Adhesive Recommendation

Vinyl coverings in sheets

Karndean I



Substrate Preparation

Substrates (for example)	Gypsum based substrates	Concrete / Cement based substrates	Prefabricated boards (OSB, particle board)
Primer (for example)	SCHÖNOX KH FIX (EC1 PLUS)	SCHÖNOX VD (EC1 PLUS)	
Self Leveling Compound (for example)	SCHÖNOX AP (EC1 PLUS) SCHÖNOX ZM (EC1 PLUS R) SCHÖNOX US (EC1 PLUS R)		

Floor Covering Installation

Vinyl coverings in sheets	Forest fx	
	Heterogeneous Vinyl-covering in sheets	
	Commercial and domestic areas	
Recommended Adhesive	SCHÖNOX EMICLASSIC™ Universal Pressure Sensitive Acrylic Adhesive for all Flexible Coverings (EC1 PLUS)	SCHÖNOX UNITECH Multipurpose Adhesive for carpet, vinyl and linoleum
Tool	Notched trowel 1/16" x 1/16" x 1/16"	Notched trowel 1/16" x 1/16" x 1/16"
Coverage	approx. 500 - 700 sq. ft. per unit of 3.35 gal.	approx. 630 sq. ft. per unit of 3.77 gal.

Please follow the technical information of relevant SCHÖNOX product data sheets, the advices of the manufactures of floor covering and also according to the well-known guidelines and instructions. If in doubt please do some practical tests or call the technical service under phone +49 2547 910325. More detailed information, product data sheets or laying instructions are available under www.schonox.com or www.karndean.de

KARNDEAN

I Adhesive Recommendation

Vinyl design coverings

Karndean I



Substrate Preparation

Substrates (for example)	Gypsum based substrates	Concrete / Cement based substrates	Prefabricated boards (OSB, particle board)
Primer (for example)	SCHÖNOX KH FIX (EC1 PLUS)	SCHÖNOX VD (EC1 PLUS)	
Self Leveling Compound (for example)	SCHÖNOX AP (EC1 PLUS) SCHÖNOX ZM (EC1 PLUS R) SCHÖNOX US (EC1 PLUS R)		

Floor Covering Installation

Vinyl design coverings	Projectline & Homeline - Vinyl design covering	
	Heavy thermal loading (e.g. display windows, winter garden); wet loading	
	Reaction resin adhesive	Pressure sensitive adhesive
Recommended Adhesive	SCHÖNOX PU 900 2-Component Universal Polyurethane Adhesive (EC 1 PLUS R)	SCHÖNOX EMICLASSIC™ Universal Pressure Sensitive Acrylic Adhesive for all Flexible Coverings (EC1 PLUS)
Tool	Notched trowel 1/8" x 1/8" x 1/16"	Notched trowel 1/16" x 1/16" x 1/16"
Coverage	approx. 105 sq. ft. per unit of 1.09 gal.	approx. 500 - 700 sq. ft. per unit of 3.35 gal.

Please follow the technical information of relevant SCHÖNOX product data sheets, the advices of the manufactures of floor covering and also according to the well-known guidelines and instructions. If in doubt please do some practical tests or call the technical service under phone +49 2547 910325. More detailed information, product data sheets or laying instructions are available under www.schonox.com or www.karndean.de

I Adhesive Recommendation

homogeneous and heterogeneous floorings

Mannington I



Substrate Preparation

Substrates (for example)	Gypsum based substrates	Concrete / Cement based substrates	Prefabricated boards (OSB, particle board)
Primer (for example)	SCHÖNOX KH FIX EC1 PLUS)	SCHÖNOX VD (EC1 PLUS)	
Self Leveling Compound (for example)	SCHÖNOX AP (EC1 PLUS) SCHÖNOX ZM (EC1 PLUS R) SCHÖNOX US (EC1 PLUS R)		

Floor Covering Installation

homogeneous and heterogeneous floorings	LIFELINES / BIOSPEC / FINE FIELDS ARCHITEXTURES / MAGNA / INSPIRATIONS / BRUSHWORK / COLOR POINT / SOLID POINT INSIGHT / CUSTOMSPEC II / MANNINGTON ASSURANCE II REALITIES / MOMENTUM / ESSENTIALS / DESIGNER ESSENTIALS		
Recommended Adhesive	SCHÖNOX EMICLASSIC™ Universal Pressure Sensitive Acrylic Adhesive for all Flexible Coverings (EC1 PLUS)		SCHÖNOX UNITECH Multipurpose Adhesive for carpet, vinyl and linoleum
Tool	Notched trowel 1/16" x 1/16" x 1/16"		Notched trowel 1/16" x 1/16" x 1/16"
Coverage	approx. 500 - 700 sq. ft. per unit of 3.35 gal.		approx. 630 sq. ft. per unit of 3.77 gal.

Please follow the technical information of relevant SCHÖNOX product data sheets, the advices of the manufactures of floor covering and also according to the well-known guidelines and instructions. If in doubt please do some practical tests or call the technical service under phone +49 2547 910325. More detailed information, product data sheets or laying instructions are available under www.schonox.com or www.mannington.com



I Adhesive Recommendation
textile
Mannington I



Substrate Preparation

Substrates (for example)	Gypsum based substrates	Concrete / Cement based substrates	Prefabricated boards (OSB, particle board)
Primer (for example)	SCHÖNOX KH FIX EC1 PLUS)	SCHÖNOX VD (EC1 PLUS)	
Self Leveling Compound (for example)	SCHÖNOX AP (EC1 PLUS) SCHÖNOX ZM (EC1 PLUS R) SCHÖNOX US (EC1 PLUS R)		

Floor Covering Installation

textile floorings / carpet backings	integraph / ultrabac plus		Infinity modular
Recommended Adhesive	SCHÖNOX EMICLASSIC™ Universal Pressure Sensitive Acrylic Adhesive for all Flexible Coverings (EC1 PLUS)	SCHÖNOX UNITECH Multipurpose Adhesive for carpet, vinyl and linoleum	SCHÖNOX MULTIFIX tackifier for carpet tiles (EC 1)
Tool	Notched trowel 1/8" x 1/8" x 1/16" or /32" x 3/32" x 3/32"	Notched trowel 1/8" x 1/8" x 1/16" or /32" x 3/32" x 3/32"	roller
Coverage	approx. 320 -430 sq. ft. per unit of 3.35 gal.	approx. 450 sq. ft. per unit of 3.77 gal.	1250 sq. ft. per unit of 2.28 gal.

Please follow the technical information of relevant SCHÖNOX product data sheets, the advices of the manufactures of floor covering and also according to the well-known guidelines and instructions. If in doubt please do some practical tests or call the technical service under phone +49 2547 910325. More detailed information, product data sheets or laying instructions are available under www.schonox.com or www.mannington.com



I Adhesive Recommendation

Mondo I



Substrate Preparation

Substrates (for example)	Gypsum based substrates	Concrete / Cement based substrates	Prefabricated boards (OSB, particle board)
Primer (for example)	SCHÖNOX KH FIX EC1 PLUS)	SCHÖNOX VD (EC1 PLUS)	
Self Leveling Compound (for example)	SCHÖNOX AP (EC1 PLUS) SCHÖNOX ZM (EC1 PLUS R) SCHÖNOX US (EC1 PLUS R)		

Floor Covering Installation

quality	GEODE, PUNTI & (DL), UNITO, TONO, FUTURA & (DL), ALBA, BOLLO, STEP, MURALE, ARDESSIA, SAFTY, LOGES		
	thickness: < 3,2 mm dispersion adhesive possible (ask in case of increased thermal or physical load) >3,2 - 4,0 mm reaction-adhesive (dispersion adhesive only on demand) > 4,0 mm reaction-adhesive		
Recommended Adhesive	SCHÖNOX EMICLASSIC™ Universal Pressure Sensitive Acrylic Adhesive for all Flexible Coverings (EC1 PLUS)	SCHÖNOX PU 900* 2-Component Universal Polyurethane Adhesive PLUS R) (EC 1	
Tool	Notched trowel 1/16" x 1/16" x 1/16"		Notched trowel 1/8" x 1/8" x 1/16"
Coverage	approx. 500 - 700 sq. ft. per unit of 3.35 gal.		approx. 105 sq. ft. per unit of 1.09 gal.

Please follow the technical information of relevant SCHÖNOX product data sheets, the advices of the manufactures of floor covering and also according to the well-known guidelines and instructions. If in doubt please do some practical tests or call the technical service under phone +49 2547 910325. More detailed information, product data sheets or laying instructions are available under www.schonox.com or www.mondo.lu

*Only for laying tiles



I Adhesive Recommendation

Mondo I



Substrate Preparation

Substrates (for example)	Gypsum based substrates	Concrete / Cement based substrates	Prefabricated boards (OSB, particle board)
Primer (for example)	SCHÖNOX KH FIX EC1 PLUS)	SCHÖNOX VD (EC1 PLUS)	
Self Leveling Compound (for example)	SCHÖNOX AP (EC1 PLUS) SCHÖNOX ZM (EC1 PLUS R) SCHÖNOX US (EC1 PLUS R)		

Floor Covering Installation

quality	AKUSTIKO
	thickness of the covering: 4,0 mm
Recommended Adhesive	SCHÖNOX EMICLASSIC™ Universal Pressure Sensitive Acrylic Adhesive for all Flexible Coverings (EC1 PLUS)
Tool	Notched trowel 1/16" x 1/16" x 1/16"
Coverage	approx. 500 - 700 sq. ft. per unit of 3.35 gal.

Please follow the technical information of relevant SCHÖNOX product data sheets, the advices of the manufactures of floor covering and also according to the well-known guidelines and instructions. If in doubt please do some practical tests or call the technical service under phone +49 2547 910325. More detailed information, product data sheets or laying instructions are available under www.schonox.com or www.mondo.lu



I Adhesive Recommendation

heterogeneous / acoustics and safety coverings

Tarkett I



Substrate Preparation

Substrates (for example)	Gypsum based substrates	Concrete / Cement based substrates	Prefabricated boards (OSB, particle board)
Primer (for example)	SCHÖNOX KH FIX (EC1 PLUS)	SCHÖNOX VD (EC1 PLUS)	
Self Leveling Compound (for example)	SCHÖNOX AP (EC1 PLUS) SCHÖNOX ZM (EC1 PLUS R) SCHÖNOX US (EC1 PLUS R)		

Floor Covering Installation

heterogeneous / acoustics and safety coverings	Granit Acoustiflor, Century, Acczent, Tapiflex, Eminent Safe, Titan, Safetred, Aquarelle Wallgard		
Recommended Adhesive	SCHÖNOX EMICLASSIC™ Universal Pressure Sensitive Acrylic Adhesive for all Flexible Coverings (EC1 PLUS)		SCHÖNOX UNITECH Multipurpose Adhesive for carpet, vinyl and linoleum
Tool	Notched trowel 1/16" x 1/16" x 1/16"		Notched trowel 1/16" x 1/16" x 1/16"
Coverage	approx. 500 - 700 sq. ft. per unit of 3.35 gal.		approx. 630 sq. ft. per unit of 3.77 gal.

Please follow the technical information of relevant SCHÖNOX product data sheets, the advices of the manufactures of floor covering and also according to the well-known guidelines and instructions. If in doubt please do some practical tests or call the technical service under phone +49 2547 910325. More detailed information, product data sheets or laying instructions are available under www.schonox.com or www.tarkett.com



I Adhesive Recommendation

Homogeneous coverings

Tarkett I



Substrate Preparation

Substrates (for example)	Gypsum based substrates	Concrete / Cement based substrates	Prefabricated boards (OSB, particle board)
Primer (for example)	SCHÖNOX KH FIX (EC1 PLUS)	SCHÖNOX VD (EC1 PLUS)	
Self Leveling Compound (for example)	SCHÖNOX AP (EC1 PLUS) SCHÖNOX ZM (EC1 PLUS R) SCHÖNOX US (EC1 PLUS R)		

Floor Covering Installation

Homogeneous coverings	Megalit, Stone, Eminent, Optima, Granit, Eclipse, Somplan Plus, Standard, Marleyflor Plus, Marleyflex		
Recommended Adhesive	SCHÖNOX EMICLASSIC™ Universal Pressure Sensitive Acrylic Adhesive for all Flexible Coverings (EC1 PLUS)	SCHÖNOX UNITECH Multipurpose Adhesive for carpet, vinyl and linoleum	SCHÖNOX PU 900 2-Component Universal Polyurethane Adhesive (EC 1 PLUS R)
Tool	Notched trowel 1/16" x 1/16" x 1/16"	Notched trowel 1/16" x 1/16" x 1/16"	Notched trowel 1/8" x 1/8" x 1/16"
Coverage	approx. 500 - 700 sq. ft. per unit of 3.35 gal.	approx. 630 sq. ft. per unit of 3.77 gal.	approx. 105 sq. ft. per unit of 1.09 gal.

Please follow the technical information of relevant SCHÖNOX product data sheets, the advices of the manufactures of floor covering and also according to the well-known guidelines and instructions. If in doubt please do some practical tests or call the technical service under phone +49 2547 910325. More detailed information, product data sheets or laying instructions are available under www.schonox.com or www.tarkett.com

I Adhesive Recommendation

Luxury Vinyl Tile

Tarkett I



Substrate Preparation

Substrates (for example)	Gypsum based substrates	Concrete / Cement based substrates	Prefabricated boards (OSB, particle board)
Primer (for example)	SCHÖNOX KH FIX (EC1 PLUS)	SCHÖNOX VD (EC1 PLUS)	
Self Leveling Compound (for example)	SCHÖNOX AP (EC1 PLUS) SCHÖNOX ZM (EC1 PLUS R) SCHÖNOX US (EC1 PLUS R)		

Floor Covering Installation

Floor covering	iD Essential 30, iD Selection 40, iD Inspiration 70, iD Inspiration 55		
Loading	Residential / Commercial		Heavy Loadings (e. g. display windows, conservatory, wet rooms)
Recommended Adhesive	SCHÖNOX ROLL AND GO® Rollable Acrylic Adhesive for Luxury Vinyl Tiles (EC 1)	SCHÖNOX EMICLASSIC™ Universal Pressure Sensitive Acrylic Adhesive for all Flexible Coverings (EC1 PLUS)	SCHÖNOX PU 900 2-Component Universal Polyurethane Adhesive (EC 1 PLUS R)
Tool	SCHÖNOX ROLL AND GO ROLLER	Notched trowel 1/16" x 1/16" x 1/16"	Notched trowel 1/8" x 1/8" x 1/16"
Coverage	approx. 540 sq. ft. per Set (containing adhesive, primer and the required tools)	approx. 500 - 700 sq. ft. per unit of 3.35 gal.	approx. 105 sq. ft. per unit of 1.09 gal.

The requirements of the relevant valid standards, guidelines and data sheets apply. Do not install underlayment or topping before the substrate has dried thoroughly. Follow the technical product information of the floor coverings manufacturers regarding specific substrate requirements for their coverings. If in doubt we recommend to test in a small area.



I Adhesive Recommendation

Vinyl design deals

Tarkett I



Substrate Preparation

Substrates (for example)	Gypsum based substrates	Concrete / Cement based substrates	Prefabricated boards (OSB, particle board)
Primer (for example)	SCHÖNOX KH FIX (EC1 PLUS)	SCHÖNOX VD (EC1 PLUS)	
Self Leveling Compound (for example)	SCHÖNOX AP (EC1 PLUS) SCHÖNOX ZM (EC1 PLUS R) SCHÖNOX US (EC1 PLUS R)		

Floor Covering Installation

Vinyl design deals	I.D. Moduline, Esteem, Reflections, Premier	
loading	increased thermal influence (e.g. display windows, winter garden); wet loading	
	reaction resin adhesive	pressure sensitive adhesion* + wet-bonding
Recommended Adhesive	SCHÖNOX PU 900 2-Component Universal Polyurethane Adhesive (EC 1 PLUS R)	SCHÖNOX EMICLASSIC™ Universal Pressure Sensitive Acrylic Adhesive for all Flexible Coverings (EC1 PLUS)
Tool	Notched trowel 1/8" x 1/8" x 1/16"	Notched trowel 1/16" x 1/16" x 1/16"
Coverage	approx. 105 sq. ft. per unit of 1.09 gal.	approx. 500 - 700 sq. ft. per unit of 3.35 gal.

Please follow the technical information of relevant SCHÖNOX product data sheets, the advices of the manufactures of floor covering and also according to the well-known guidelines and instructions. If in doubt please do some practical tests or call the technical service under phone +49 2547 910325. More detailed information, product data sheets or laying instructions are available under www.schonox.com or www.tarkett.com

* Pressure to sensitive ahesion allows the covering a higher size alternation / dimensional change.

