Revision Date 02/22/2018 Print Date 02/22/2018

1. Identification

Product name : SCHÖNOX® XM

Supplier : HPS North America, Inc.,

511 Wilhite Street, Florence, AL 35630

USA

Telephone : 256.246.0345

Telefax : 256.246.0346

E-mail address : info@hpssubfloors.com

Emergency telephone : GBK/Infotrac ID 108313 at 1 800 535 5053 (USA)

INTERNATIONAL: (001) 352 323 3500

Recommended use of the chemical and restrictions on

use

For further information, refer to product data sheet.

2. Hazards identification

GHS Classification

Skin corrosion, Category 1C H314: Causes severe skin burns and eye damage.

Serious eye damage, Category 1

Carcinogenicity, Category 1A (Inhalation)

Specific target organ systemic toxicity
H318: Causes serious eye damage.

H350i: May cause cancer by inhalation.

H335: May cause respiratory irritation.

system

Specific target organ systemic toxicity - H372: Causes damage to organs through

repeated exposure, Category 1, Lungs prolonged or repeated exposure.

GHS label elements

Hazard pictograms







Signal Word : Danger

single exposure, Category 3, Respiratory

Hazard Statements : H314 Causes severe skin burns and eye damage.

H335 May cause respiratory irritation. H350i May cause cancer by inhalation.

H372 Causes damage to organs (Lungs) through prolonged or

repeated exposure.

Precautionary Statements : P101 If medical advice is needed, have product container or

label at hand.

P102 Keep out of reach of children. P103 Read label before use.

Prevention:

Revision Date 02/22/2018 Print Date 02/22/2018

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.

P270 Do not eat, drink or smoke when using this product.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P281 Use personal protective equipment as required.

Response:

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308 + P313 IF exposed or concerned: Get medical advice/ attention.

P310 Immediately call a POISON CENTER/doctor.

P363 Wash contaminated clothing before reuse.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

See Section 11 for more detailed information on health effects and symptoms.

There are no hazards not otherwise classified that have been identified during the classification process.

There are no ingredients with unknown acute toxicity used in a mixture at a concentration >= 1%.

3. Composition/information on ingredients

Pure substance/mixture : Mixture

Hazardous ingredients

Chemical name	CAS-No.	Concentration (%)
Quartz (SiO2)	14808-60-7	>= 25 - < 50 %
Portland cement	65997-15-1	>= 5 - < 10 %
Quartz (SiO2) <5µm	14808-60-7	>= 0.1 - < 1 %

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Revision Date 02/22/2018 Print Date 02/22/2018

4. First aid measures

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water.

Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with

difficulty.

In case of eye contact : Small amounts splashed into eyes can cause irreversible

tissue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses.

Keep eye wide open while rinsing.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Do not induce vomiting without medical advice.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Take victim immediately to hospital.

Most important symptoms and effects, both acute and

delayed

: Prolonged exposure can cause silicosis.

Health injuries may be delayed.

corrosive effects irritant effects

carcinogenic effects

Cough

Respiratory disorder

Dermatitis

See Section 11 for more detailed information on health effects

and symptoms.

Causes serious eye damage. May cause respiratory irritation. May cause cancer by inhalation.

Causes damage to organs through prolonged or repeated

exposure.

Causes severe burns.

Protection of first-aiders : Move out of dangerous area.

Consult a physician.

Show this material safety data sheet to the doctor in

attendance.

Notes to physician : Treat symptomatically.

5. Fire-fighting measures

Revision Date 02/22/2018 Print Date 02/22/2018

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Specific extinguishing

methods

: Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment

for fire-fighters

: In the event of fire, wear self-contained breathing apparatus.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.

Avoid breathing dust.

Deny access to unprotected persons.

Environmental precautions : Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up

Pick up and arrange disposal without creating dust. Keep in suitable, closed containers for disposal.

7. Handling and storage

Advice on safe handling : Avoid formation of respirable particles.

Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Follow standard hygiene measures when handling chemical

products.

Conditions for safe storage : Prevent unauthorized access.

Store in original container. Keep in a well-ventilated place. Observe label precautions.

Store in accordance with local regulations.

Materials to avoid : No data available

8. Exposure controls/personal protection

Component	CAS-No.	Basis **	Value	Exposure limit(s)* / Form of exposure
Quartz (SiO2)	14808-60-7	OSHA Z-3	TWA	10 mg/m3 /

Revision Date 02/22/2018

Print Date 02/22/2018

				%SiO2+2 respirable
		OSHA Z-3	TWA	250 mppcf / %SiO2+5 respirable
		OSHA P0	TWA	0.1 mg/m3 Respirable fraction
		ACGIH	TWA	0.025 mg/m3 Respirable fraction
		OSHA Z-1	TWA	0.05 mg/m3 Respirable dust
Portland cement	65997-15-1	ACGIH	TWA	1 mg/m3 Respirable fraction
		OSHA Z-1	TWA	15 mg/m3 total dust
		OSHA Z-1	TWA	5 mg/m3 respirable fraction
		OSHA Z-3	TWA	50 Million particles per cubic foot Dust
		OSHA P0	TWA	10 mg/m3 Total dust
		OSHA P0	TWA	5 mg/m3 respirable dust fraction
Limestone	1317-65-3	OSHA Z-1	TWA	15 mg/m3 total dust
		OSHA Z-1	TWA	5 mg/m3 respirable fraction
		OSHA P0	TWA	15 mg/m3 Total
		OSHA P0	TWA	5 mg/m3 Respirable fraction
		OSHA P0	TWA	15 mg/m3 Total dust
		OSHA P0	TWA	5 mg/m3 respirable dust fraction

Revision Date 02/22/2018

Print Date 02/22/2018

calcium sulfate	7778-18-9	OSHA Z-1	TWA	15 mg/m3 total dust
		OSHA Z-1	TWA	5 mg/m3 respirable fraction
		OSHA P0	TWA	15 mg/m3 Total
		OSHA P0	TWA	5 mg/m3 Respirable fraction
		OSHA P0	TWA	15 mg/m3 Total dust
		OSHA P0	TWA	5 mg/m3 respirable dust fraction
		ACGIH	TWA	10 mg/m3 Inhalable fraction
		ACGIH	TWA	10 mg/m3 Inhalable fraction
Quartz (SiO2) <5µm	14808-60-7	OSHA Z-3	TWA	10 mg/m3 / %SiO2+2 respirable
		OSHA Z-3	TWA	250 mppcf / %SiO2+5 respirable
		OSHA P0	TWA	0.1 mg/m3 Respirable fraction
		ACGIH	TWA	0.025 mg/m3 Respirable fraction
		OSHA Z-1	TWA	0.05 mg/m3 Respirable dust

^{*}The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

**Basis

ACGIH. Threshold Limit Values (TLV)

OSHA P0. Table Z-1, Limit for Air Contaminat (1989 Vacated Values)

OSHA P1. Permissible Exposure Limits (PEL), Table Z-1, Limit for Air Contaminant

OSHA P2. Permissible Exposure Limits (PEL), Table Z-2

OSHA Z3. Table Z-3, Mineral Dust

Revision Date 02/22/2018 Print Date 02/22/2018

Engineering measures

: Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

Personal protective equipment

Respiratory protection : Use a properly fitted NIOSH approved air-purifying or air-fed

respirator complying with an approved standard if a risk

assessment indicates this is necessary.

The filter class for the respirator must be suitable for the

maximum expected contaminant concentration

(gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained

breathing apparatus must be used.

Hand protection

Remarks : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling

chemical products if a risk assessment indicates this is

necessary.

Eye protection : Safety eyewear complying with an approved standard should

be used when a risk assessment indicates this is necessary.

Skin and body protection : Choose body protection in relation to its type, to the

concentration and amount of dangerous substances, and to

the specific work-place.

Hygiene measures : Avoid contact with skin, eyes and clothing.

Wash hands before breaks and immediately after handling the

product.

Remove contaminated clothing and protective equipment

before entering eating areas.

Wash thoroughly after handling.

Avoid breathing dust.

9. Physical and chemical properties

Appearance : powder
Color : gray

Odor : characteristic

Odor Threshold : No data available

Flash point : Note: Not applicable

Ignition temperature : No data available

Decomposition temperature : No data available

Revision Date 02/22/2018 Print Date 02/22/2018

Lower explosion limit (Vol%) : No data available

Upper explosion limit (Vol%) : No data available

Flammability (solid, gas) : No data available

Oxidizing properties : No data available

pH : 10 - 11

at

68 °F (20 °C)

Melting point/range /

Freezing point

No data available

Boiling point/boiling range : No data available

Vapor pressure : No data available

Density : ca.1.22 g/cm3

at 68 °F (20 °C)

Water solubility : No data available

Partition coefficient: n-

octanol/water

: No data available

Viscosity, dynamic : No data available

Viscosity, kinematic : Note: Not applicable

Relative vapor density : No data available

Evaporation rate : No data available

Burning rate : No data available

Volatile organic compounds

(VOC) content

Not applicable

: No data available

10. Stability and reactivity

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous

Conditions to avoid

reactions

: Stable under recommended storage conditions.

Incompatible materials : No data available

11. Toxicological information

Revision Date 02/22/2018 Print Date 02/22/2018

Acute toxicity

Not classified based on available information.

Skin corrosion/irritation

Causes severe burns.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitization

Skin sensitization: Not classified based on available information. Respiratory sensitization: Not classified based on available information.

Product:

Remarks: Product contains Portland cement which contains a chromate reducing agent. If the storage conditions are not appropriate (exposure to humidity) or the storage period is exceeded, the effectiveness of the reducing agent can be diminished prematurely and the product may become skin sensitizing.

Germ cell mutagenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

May cause respiratory irritation.

STOT-repeated exposure

Causes damage to organs (Lungs) through prolonged or repeated exposure.

Prolonged exposure can cause silicosis.

Aspiration toxicity

Not classified based on available information.

Carcinogenicity

May cause cancer by inhalation.

IARC Group 1: Carcinogenic to humans

Quartz (SiO2) 14808-60-7 Quartz (SiO2) <5μm 14808-60-7

NTP Known to be human carcinogen

Quartz (SiO2) 14808-60-7 Quartz (SiO2) <5µm 14808-60-7

12. Ecological information

Other information Do not empty into drains; dispose of this material and its

container in a safe way.

13. Disposal considerations

Revision Date 02/22/2018 Print Date 02/22/2018

Disposal methods

Waste from residues : Disposal of this product, solutions and any by-products should

> at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Empty containers should be taken to an approved waste Contaminated packaging

handling site for recycling or disposal.

14. Transport information

DOT

Not dangerous goods

IATA

Not dangerous goods

IMDG

Not dangerous goods

Special precautions for user

No data available

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

15. Regulatory information

TSCA list All chemical substances in this product are either listed on the

TSCA Inventory or are in compliance with a TSCA Inventory

exemption.

EPCRA - Emergency Planning and Community Right-to-Know

CERCLA Reportable Quantity

Ingredients	CAS-No.	Component RQ (lbs)
Ethylene oxide	75-21-8	10
1,4-dioxane	123-91-1	100
cyclohexane	110-82-7	1000
sodium hydroxide	1310-73-2	1000

SARA 304 Extremely Hazardous Substances Reportable Quantity

Ingredients	CAS-No.	Component RQ (lbs)
Ethylene oxide	75-21-8	10

SARA 311/312 Hazards : Skin corrosion or irritation

Serious eye damage or eye irritation

Carcinogenicity

Specific target organ toxicity (single or repeated exposure)

Revision Date 02/22/2018 Print Date 02/22/2018

SARA 302 : This material does not contain any components with a section

302 EHS TPQ.

SARA 313 : This material does not contain any chemical components with

> known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Air Act

Ozone-Depletion

Potential

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act

Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

California Prop 65

MARNING: Cancer and Reproductive Harm -

www.P65Warnings.ca.gov

16. Other information

HMIS Classification



Caution: HMIS® rating is based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® rating is not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® rating is to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). Please note HMIS® attempts to convey full health warning information to all employees.

Notes to Reader

The information contained in this Safety Data Sheet applies only to the actual Product name identified and described herein ("Product Name"). This information is not intended to address, nor does it address the use or application of the identified Product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified Product that is believed to be reliable as of the date hereof. Prior to each use of the Product, the user must always read and follow the warnings and instructions on the Product's most current product label, Product Data Sheet, and Safety Data Sheet, which are available at www.schonox.us and/or the telephone number listed in Section 1 of this SDS.

Revision Date 02/22/2018

Print Date 02/22/2018

SCHÖNOX HPS NORTH AMERICA, A BUSINESS UNIT OF HPS NORTH AMERICA, INC. (HPS SCHÖNOX), MAKES NO WARRANTIES EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO, ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, AND ASSUME NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. HPS SCHÖNOX SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

Revision Date 02/22/2018

Material number: 546878