

# SCHÖNOX PU 900

## 2-Part Universal Polyurethane Adhesive

Suitable for bonding vinyl and rubber floor coverings as well as other materials on porous and non-porous substrates in interior and exterior areas.



### Product characteristics

- EMICODE EC 1<sup>PLUS</sup>: very low emission regulated
- for interior and exterior use
- solvent-free
- water free
- rapid hardening
- non-shrinking even in thicker layers
- suitable on underfloor heating systems
- low odor
- long open time
- easy to apply
- high strength

### Applications

**SCHÖNOX PU 900 is suitable for bonding floor coverings, such as:**

- sheet vinyl
- synthetic rubber coverings in sheets
- linoleum coverings in sheets
- rubber granulate underlays
- suitable artificial grass

**as well as for repairing of non-structural cracks in porous and non-porous substrates in heavy loaded interior areas.**

### Requirements of substrate

- Subfloors must be smooth, sound, clean, dry and free of any contaminants which may hinder adhesion.
- Surface treatments or any "friable" areas of the subfloor must be mechanically removed and the subfloor repaired with SCHÖNOX leveling compounds as required.
- Old water-soluble adhesives should be removed completely, old water-resistant adhesives should be mechanically removed as far as possible. The complete mechanical removal of cutback (i.e. grinding, sanding, blasting) can be hazardous as old cutback adhesive may contain asbestos. Do not sand or grind adhesive residue. Refer to the Resilient Floor Covering Institute's publication "recommended work practice for removal of resilient floor coverings" for instruction. Prime remaining adhesive residues accordingly.
- All slabs on or below grade level must be known to have an intact vapor retarder directly beneath the concrete in conformance to the relevant standards. If in doubt, please contact our SCHÖNOX representative for further advise.
- With subsequent laying of floor coverings on cementitious substrates, where moisture readings are above 85% RH or 6 lbs./1000 sq.ft./24hrs then application of SCHÖNOX MR 18, SCHÖNOX EPA or SCHÖNOX EPA RAPID may be used to suppress residual moisture (see data

sheet). Always follow the directions of the floor covering manufacturer regarding the maximum allowable moisture content and test the substrate prior to installing SCHÖNOX PU 900.

- Gypsum substrates should always be dry. Do not use moisture mitigation systems on gypsum substrates.
- Always follow the floor covering manufacturers guidelines regarding specific substrate requirements for their coverings.
- Some unevenness in the substrate can be leveled with SCHÖNOX PU 900.
- The requirements of the relevant valid standards, guidelines and data sheets apply.

### Recommended method of working

- Wear rubber gloves and protective goggles. Add the hardener component (B) to the resin component (A) and form a homogeneous mixture using a mixer.
- To guarantee a homogenous mixture, transfer the mixture to a clean container and repeat the mixing process.
- Floor coverings must always be conditioned, unstressed and lay flat without any deformation. Always acclimate the floor covering accordingly following the manufacturers guidelines.
- Empty the adhesive out of the pail and spread evenly on the substrate using a suitable notched trowel within the open time.
- Lay the covering into the fresh adhesive bed, rub down or roll the covering using a metal roller. After 1 – 2 hours roll again.
- SCHÖNOX PU 900 may be used as a crack repair compound to fill or seal dormant cracks or joints. The fresh adhesive is pressed into using a flat trowel. SCHÖNOX RENOTEX may be embedded into PU 900 to reinforce the repair if required. The surface of the fresh PU 900 may be sand broadcasted to ensure a suitable bond to following materials. Alternatively prime with SCHÖNOX SHP after drying.
- Clean tool immediately after use with appropriate cleaner.

### Packaging

- 2-Component system:
  - 0.86 gallon component A (resin) in plastic container
  - 0.23 gallon component B (hardener) in plastic container

### Technical data

- basis: solvent-free, two-part urethane,
  - comp. A: resin with special additives
  - comp. B: polyisocyanate hardener
- colour: beige
- density: 1.74 kg/l (mixture)
- storage temperature: not below 32 °F
- temperature resistance: up to 120 °F
- working temperature: not below 59 °F floor temperature
- coverage per unit when applied with
  - notched trowel 1/8"x1/8"x1/16": approx. 105 sq.ft.
- pot life: approx. 40 min at 65 °F
- waiting time: none
- open time: approx. 70 min
- drying time: approx. 24 hours
- final strength: after approx. 24-48 hours

All values are approximate, are subject to local climatic fluctuations based upon conditions at 70°F with atmosphere of less than 65 % relative humidity following the recommended mixing ratio. Do not install underlayment or topping before the substrate has dried thoroughly.



# SCHÖNOX PU 900

- Shelf life: 12 months unopened.
- Remove any skin that has formed, do not stir in.

## Disposal

- Empty containers and dispose of in accordance with federal, state and local waste disposal regulations.

## VOC Content

- 0g/l (calculated) SCAQMD 1168

## LEED

May contribute to LEED v4 in categories:

- EQc2 - 3 points  
Low-Emitting Materials
- MRc2 - 1 point  
Environmental Product Declaration
- MRc4 - 1 point  
Material Ingredients

## Environmental Product Declaration (EPD)

- Declaration number:  
EPD-DIV-20140063-IBG1-EN

## Precautions

- Always install an adequate number of properly located test areas, to include the finish flooring, to determine the suitability of the product for its intended use. As floor coverings vary, always contact and rely upon the floor covering manufacturer for specific directions such as maximum allowable moisture content, adhesive selection, and intended end use of the product.
- Avoid eye and skin contact. Close container after each use. Do not reuse container. Do not flush adhesive down drains, sewers or waterways.

Prior to each use of any SCHÖNOX product, the user must always read and follow the warnings and instructions on the product's most current product label, Product Data Sheet and Safety Data Sheet which are available at [www.hpsubfloors.com](http://www.hpsubfloors.com), or by calling the HPS SCHÖNOX Technical Service Department at 855-391-2649. Nothing contained in any SCHÖNOX materials relieves the user of the obligation to read and follow the warnings and instruction for each SCHÖNOX product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to product use. This product data sheet supersedes all previous editions.



Management system certified  
to ISO 9001 and 14001 by SQS.

### In North America provided by:

HPS North America, Inc

Phone: 256.246.0345

Fax: 256.246.0346

Email: [info@hpsubfloors.com](mailto:info@hpsubfloors.com)

<http://www.hpsubfloors.com>



KEEP CONTAINER TIGHTLY CLOSED • KEEP OUT OF REACH OF CHILDREN • NOT FOR INTERNAL CONSUMPTION • FOR INDUSTRIAL USE ONLY • FOR PROFESSIONAL USE ONLY  
SCHÖNOX products are supplied in the USA by SCHÖNOX HPS North America, a business unit of HPS North America, Inc. (HPS SCHÖNOX).

For further information and advice regarding transportation, handling, storage and disposal of chemical products, users should refer to the actual Safety Data Sheets containing physical, ecological, toxicological and other safety related data. Read the current actual Safety Data Sheet before using the product. In case of emergency, call GBK/Infotrac ID 108313 at 1 800 535 5053 (USA) or 001 352 323 3500 (International). HPS SCHÖNOX warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within shelf life. User determines suitability of product for intended use and assumes all risks. Buyer's sole remedy shall be limited to the purchase price or replacement of product exclusive of labor or cost of labor. NO OTHER WARRANTIES EXPRESSED OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. HPS SCHÖNOX SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. HPS SCHÖNOX SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS. Sale of SCHÖNOX products are subject to the Terms and Conditions of Sale which are available at [www.schonox.us](http://www.schonox.us).