


SCHÖNOX HA BECAUSE THERE'S NOTHING FUNNY ABOUT WATERPROOFING.



READY-MIXED, ROLLABLE WATERPROOF SEALING MEMBRANE & CRACK ISOLATION

Schönox knows that dealing with water issues can soak an installer. If one step fails, it can ruin the entire project, costing both time and money. Use Schönox HA for installations of waterproof sealings under ceramic tiles in residential and commercial wet areas. Ready mixed, rapid-drying, easy to apply and proven to work.



SCHÖNOX HA

READY-MIXED, ROLLABLE WATERPROOF SEALING MEMBRANE & CRACK ISOLATION

Suitable for waterproofing under ceramic tiles in residential and commercial interior wet areas. Schönox HA acts as a crack-isolation membrane without waterproofing requirements, applied in one coat at required thickness.



RAPID DRYING



MEETS ANSI STANDARDS



WATERTIGHT



TROWELABLE

PRODUCT CHARACTERISTICS

- Interior use only
- Very low emissions
- One or two coat system
- Ready mixed
- Rapid-drying
- Highly elastic
- Resistant against aging
- Easy to apply
- Ideal for trowel or roller application
- Solvent free
- Crack isolation over nonstructural cracks up to 1/16"

RECOMMENDED APPLICATION DETAILS

Schönox HA is suitable for sealing of:

- Concrete, cement substrates
- Masonry (fully grouted)
- Gypsum based substrates (compressive strength >2500 psi)
- Old substrates such as ceramic tiles
- Cement plaster, lime-cement plaster
- Gypsum plaster
- Wall panels of lightweight concrete
- Gypsum board
- Plywood, OSB boards

PRIMING

- Very porous and all gypsum based substrates: prime with SCHÖNOX KH FIX, drying time at least 1 hour

TECHNICAL DATA

- Basis: synthetic resin dispersion
- Color: blue-grey
- Application temperature: not below + 5°C / 41°F
- Ready for covering:
 - after approx. 3 – 5 hours (depending on conditions and thickness)
- Coverage: (at minimum thickness)
 - approx. 200 sq.ft. per unit of 22 kg/3.8 gal.

PACKAGING

- 22 kg / 3.8 gal. in a plastic container



LEED V4.1 ID+C, BD+C

Contributes to LEED v4.1 certification of projects in these categories:

- EQc2 – 3 points Low-Emitting Materials
- MRc2 – 1 point Environmental Product Declaration
- MRc4 – 1 point Material Ingredients



Refer to Technical Data Sheets for additional, current information. Available on the Schönox app and at hpsubfloors.com.

Take your business to a whole new level.
Call 855.391.2649 or visit hpsubfloors.com to learn
how your projects run smoother with Schönox On It.



BUILDING TRUST

