

SCHÖNOX PGH

Rapid Curing, Two-Part, Crack Repair Compound

suitable for filling screed cracks and dummy joints and for bonding nail battens, metal sections as well as natural and artificial stones. Renovation clips included.



Product characteristics

- waterfree
- for interior and exterior use
- low consumption / high coverage
- highly loadable
- rapid hardening
- extendable with aggregate
- low viscosity
- good penetrability
- suitable on floor heating systems

Applications

SCHÖNOX PGH is suitable:

- for filling cracks and dummy joints
- for bonding nail-battens, metal sections, natural and artificial stones

Recommended method of working

- Add the hardener component (B) to the resin component (A) and form a homogeneous mixture by using a mixer.
- The working time can be influenced by the dosage of hardener. When using the full hardener tube the working time is approx. 7 minutes. Use mixture immediately.
- Pour SCHÖNOX PGH directly into the joints/cracks and spread the excessive material immediately using a spatula. SCHÖNOX PGH is extendable with silica sand.
- When used as a glue, apply SCHÖNOX PGH to the parts to glue and lay in immediately.
- The most efficient way to repair is to widen the crack, cut in crosswise each 10" and put in a screed renovation clip. Then fill with SCHÖNOX PGH and spread silica sand excessively into the wet surface phase of the repair compound. Do not load before SCHÖNOX PGH has cured thoroughly.
- To fill cracks in asphalt based substrates we recommend to use SCHÖNOX PU 900.
- Clean tools immediately after use with SCHÖNOX FIX CLEAN.
- Cured material can only be removed mechanically.

Packaging

- 1.0 kg / 0.126 gal tin can polyester resin
- 20 g / 0.59 oz hardener tube
- 20 screed renovation clips

Storage

- Store in cool, dry, frost-free conditions.
- Shelf life: 1 year unopened.

Disposal

- Empty packaging and dispose of in accordance with federal, state and local waste disposal regulations.

Instructions

- Always install an adequate number of properly located test areas, to include the finish flooring, to determine the suitability of the product for its intended use. As floor coverings vary, always contact and rely upon the floor covering manufacturer for specific directions such as maximum allowable moisture content, adhesive selection, and intended end use of the product.
- Low substrate temperatures and/or high ambient humidity require longer drying times.

Precautions

- Avoid eye and skin contact. Close container after each use. Do not reuse container. Do not flush primer down drains, sewers or waterways.

Technical data

- basis: polyester resin and hardener
- color: beige
- density: 1.5 kg/l
- coverage per unit to fill cracks (when approx. 1/8" wide and 1" deep): approx. 25 ft.
- storage temperature: not below 32 °F
- application temperature: not below 59 °F
- working time (depending on dosage of hardener): 7 - 15 minutes
- loadable after (depending on dosage of hardener): 30 - 60 minutes

All values are approximate, are subject to local climatic fluctuations based upon conditions at 70°F with atmosphere of less than 65 % relative humidity and depending on the dosage of the hardener. Do not install underlayment or topping before the substrate has dried thoroughly.



SCHÖNOX PGH

Prior to each use of any SCHÖNOX product, the user must always read and follow the warnings and instructions on the product's most current product label, Product Data Sheet and Safety Data Sheet which are available at www.schonox.us, or by calling the HPS SCHÖNOX Technical Service Department at 855-391-2649. Nothing contained in any SCHÖNOX materials relieves the user of the obligation to read and follow the warnings and instruction for each SCHÖNOX product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to product use. This product data sheet supersedes all previous editions.



Management system certified
to ISO 9001 and 14001 by SQS.

In North America provided by:

HPS North America, Inc

Phone: 256.246.0345

Fax: 256.246.0346

Email: info@hpsubfloors.com

<http://www.hpsubfloors.com>

KEEP CONTAINER TIGHTLY CLOSED • KEEP OUT OF REACH OF CHILDREN • NOT FOR INTERNAL CONSUMPTION • FOR INDUSTRIAL USE ONLY • FOR PROFESSIONAL USE ONLY
SCHÖNOX products are supplied in the USA by SCHÖNOX HPS North America, a business unit of HPS North America, Inc. (HPS SCHÖNOX).

For further information and advice regarding transportation, handling, storage and disposal of chemical products, users should refer to the actual Safety Data Sheets containing physical, ecological, toxicological and other safety related data. Read the current actual Safety Data Sheet before using the product. In case of emergency, call GBK/Infotrac ID 108313 at 1 800 535 5053 (USA) or 001 352 323 3500 (International). HPS SCHÖNOX warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within shelf life. User determines suitability of product for intended use and assumes all risks. Buyer's sole remedy shall be limited to the purchase price or replacement of product exclusive of labor or cost of labor. NO OTHER WARRANTIES EXPRESSED OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. HPS SCHÖNOX SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. HPS SCHÖNOX SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS. Sale of SCHÖNOX products are subject to the Terms and Conditions of Sale which are available at www.schonox.us.